

Table Specifications:

| | |
|----------------|---------------|
| Model: | F601HF |
| Material: | Aluminum |
| MOQ: | 1-100, 000pcs |
| Size: | 300 * 30 m m |
| Color: | Black |
| Weight: | 150g |
| Power: | 1500W |
| Temperature: | 150-200 °C |
| Voltage: | 110V-220V |
| Frequency: | 50/60Hz |
| Certification: | ISO 9001 |

F601HF Features:

Infar red light, far infrared ray, far infrared ray, far infrared ray, far infrared ray, far infrared ray, far infrared ray.



Far Infrared Ray Specifications:

FBT wavelength 0.76-3μm, wavelength 5-10 m m, far infrared ray, far infrared ray, far infrared ray, far infrared ray, far infrared ray.



F601HF 00 0000 0000:

- * 0 0 0000 00 00 00 0 00-0-00
- * 0000 0 000 000 00 0000 00 00 00 00 00, 00 00 0 0000 00 00 0 000000 0 0
- * 0000 0000, 0000 0 0 0000 0000 00 0000 00
- * 00 00 00, 00 00 00000 00
- * 00 1 00 0, 00 0000 0000 0000 00 0000 0000 0000
- * 3600 00 0000 000000 00 0 0 0000 00000 0000 0000 0 00 00 0000.
- * 00 0 0 00, 00000 0 0 00 00 00000 00 00

00 & 00:

| | |
|------------------|--|
| Packaging 00 00: | <ul style="list-style-type: none"> * Giftbox 00 * GB 00: 10.5 * 30 * 5.4 c m * 20pcs/ctn * 0 0 00: 56.8 * 38.5 * 24 cm * G.W.:15.0KG * 0000 0 0: 8.0KG * 1 * 20GP:11000pc * 1 * 40GP: 21800pcs |
| 00 00 00: | 30 00 00 0 |

00 00 00:

- 0000 0 00 00 00 0 0 0000. 00-0-00000. 00 00 0 0 00 0000 0000 00.
- 0 0000 straightener 0 straight 0000 00 00 0 0 00 0000 00 0000 00 0000 00.
- 1, 00 0, 00 00 00 0 0 00 0000 0000 00.
 - 2, 00 00 0 00 00 00 00 (00 00)
 - 30 0000 00 0000 00, 0000 00 00 00 00 00 00 00
 - 00 0000 4, 00 00
 - 5, 0000 000000 00 0000 0000 00 0000 0000 0000.
 - 6, 00 00 00 0 0 0000 0000 00 00 00 0000.
 - 7, 0000 0000 00 0000 00 0000 00 0000.
 - 8, 00 00 00 0 00 0 0000 0000 00.
 - 9, 00 0000 0000 00 0 0 0000 0000 0000 unclip.
 - 100 00 00 0 0000 00
 - 11, 00 00 00000, 0 000000 00 00 0000 00 00 0000 00 00 00 0000.

